SAFETY DATA SHEET

TMI Products Inc

according to Regulation (EC) No 1907/2006

Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Stick Fast 329 hardener ; 20 minute epoxy

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Adhesives, sealants

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	TMI Products Inc dba Stick Fast Inc
Place:	Peachtree City, GA 30269
Telephone:	+1 770-631-7897
Internet:	www.stickfast.com
Responsible Department:	info@stickfast.com
1.4. Emergency telephone number:	1-888-255-3924 CHEMTEL International 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Indications of danger: Xn - Harmful R phrases: Harmful by inhalation and if swallowed.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories: Acute toxicity: Acute Tox. 4 Acute toxicity: Acute Tox. 4 Hazard Statements: Harmful if swallowed or if inhaled.

2.2. Label elements

Hazardous components which must be listed on the label

2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol)

Signal word: Pictograms:

(!)

Warning GHS07

Hazard statements

H302+H332

Harmful if swallowed or if inhaled.

Precautionary statements

P270	Do not eat, drink or smoke when using this product.
P312	Call a POISON CENTER/doctor if you feel unwell.
P501	Dispose of contents/container to in accordance with official regulations.

SAFETY DATA SHEET

Stick Fast Epoxy 329 Hardener

according to Regulation (EC) No 1907/2006

Print date: 27/10/2023

Product code: 329

Page 2 of 9

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
239-044-2	2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol)	60 - 100 %
14970-87-7	Xn - Harmful R20/22	
	Acute Tox. 4, Acute Tox. 4; H302 H332	

Full text of R-, H- and EUH-phrases: see section 16.

Further Information

Product does not contain listed SVHC substances.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Take off immediately all contaminated clothing. Wash immediately with: Water and soap. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

refer to chapter 2 and 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguishing powder, Carbon dioxide (CO2), Foam, Water spray jet

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide., Carbon dioxide (CO2), Nitrogen oxides (NOx),

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006

Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 3 of 9

Sulphur oxides

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes. Wear personal protection equipment (refer to section 8).

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe vapour/aerosol. Wear personal protection equipment (refer to section 8).

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

Conditions to avoid: Generation/formation of aerosols General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed and dry.

Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances.

Further information on storage conditions

Protect against: Heat, Humidity, UV-radiation/sunlight

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

according to Regulation (EC) No 1907/2006

Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 4 of 9

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

Protective and hygiene measures

Always close containers tightly after the removal of product. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

Eye/face protection

Recommended eye protection articles: Eye glasses with side protection DIN EN 166

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves. DIN EN 374

Suitable material:

NBR (Nitrile rubber) (0,35 mm)

Breakthrough time (maximum wearing time): >480 min

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required. Respiratory protection necessary at:

insufficient ventilation

Generation/formation of aerosols

Suitable respiratory protection apparatus: Combination filtering device (EN 14387) Type A-P2/3

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

liquid clear characteristic		
		Test method
	not determined	
	not determined	
	>149 °C	
	not determined	
	clear	clear characteristic not determined not determined >149 °C

STICK FASTTM ADHESIVES

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006

TMI Products	Inc

Stick Fast Epoxy 329 Hardener				
Print date: 27/10/2023	Product code: 329	Page 5 of 9		
Flash point:	157 °C	Cleveland open cup		
Sustaining combustion:	No data available			
Explosive properties none				
Lower explosion limits:	not determined			
Upper explosion limits:	not determined			
Ignition temperature:	not determined			
Decomposition temperature:	not determined			
Oxidizing properties none				
Vapour pressure:	not determined			
Density:	1,3 g/cm³			
Water solubility:	partially soluble			
Solubility in other solvents not determined				
Viscosity / dynamic:	not determined			
Viscosity / kinematic:	not determined			
Evaporation rate:	not determined			
9.2. Other information				
Solid content:	not determined			

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against direct sunlight. Keep away from heat.

10.5. Incompatible materials

Oxidising agent, Acid

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide., Carbon dioxide (CO2), Nitrogen oxides (NOx), Sulphur oxides

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Harmful if swallowed or if inhaled.

ATEmix calculated

ATE (oral) 500,0 mg/kg; ATE (inhalative vapour) 11,00 mg/l; ATE (inhalative aerosol) 1,500 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No 1907/2006

Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 6 of 9

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
14970-87-7	1970-87-7 2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol)				
	oral	ATE	500 mg/kg		
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

according to Regulation (EC) No 1907/2006

Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 7 of 9

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances Classified as hazardous waste.

Waste disposal number of used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	Not restricted	
14.2. UN proper shipping name:	Not restricted	
14.3. Transport hazard class(es):	Not restricted	
14.4. Packing group:	Not restricted	
Inland waterways transport (ADN)		
<u>14.1. UN number:</u>	Not restricted	
14.2. UN proper shipping name:	Not restricted	
14.3. Transport hazard class(es):	Not restricted	
14.4. Packing group:	Not restricted	
Marine transport (IMDG)		
<u>14.1. UN number:</u>	Not restricted	
14.2. UN proper shipping name:	Not restricted	
14.3. Transport hazard class(es):	Not restricted	
14.4. Packing group:	Not restricted	
Air transport (ICAO)		
<u>14.1. UN number:</u>	Not restricted	
14.2. UN proper shipping name:	Not restricted	
14.3. Transport hazard class(es):	Not restricted	
14.4. Packing group:	Not restricted	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	no	
14.6. Special precautions for user		
refer to chapter 6-8		

STICK FASTTM ADHESIVES

according to Regulation (EC) No 1907/2006

Observe employment restrictions for young people. Observe employment

Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 8 of 9

TMI Products Inc

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC):	No information available.
2004/42/EC (VOC):	No information available.

Additional information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS]. Not subject to 96/82/EC

restrictions for child bearing mothers and nursing.

National regulatory information

Employment restrictions:

Water contaminating class (D):

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

2 - water contaminating

SECTION 16: Other information

Changes

Rev. 1.00; 26.05.2019, Initial release; Revision 1.01 administrative

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route **CAS Chemical Abstracts Service** DNEL: Derived No Effect Level IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) LOAEL: Lowest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level NTP: National Toxicology Program N/A: not applicable OSHA: Concerning the International Transport of Dangerous Goods by Rail) PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) SARA: Superfund Amendments and Reauthorization Act SVHC: substance of very high concern TRGS Technische Regeln für Gefahrstoffe TSCA: Toxic Substances Control Act

TMI Products Inc

according to Regulation (EC) No 1907/2006 Stick Fast Epoxy 329 Hardener

Print date: 27/10/2023

Product code: 329

Page 9 of 9

VOC: Volatile Organic Compounds VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe WGK: Wassergefährdungsklasse

Relevant R-phrases (Number and full text)

20/22 Harmful by inhalation and if swallowed.

Relevant H- and EUH-phrases (Number and full text)

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H332	Harmful if inhaled.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)