

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 1 of 9

1. Identification

Product identifier

Stick Fast Epoxy 329 Resin; 20 minute

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

Adhesives, sealants

Uses advised against

any non-intended use.

Details of the supplier of the safety data sheet

Company name: TMI Products Inc. DBA Stick Fast Inc

Place: Peachtree City, GA 30269 USA

Telephone: +1770-631-7897

Internet: www.stickfast.com

Responsible Department: info@stickfast.com

Emergency phone number: +1-888-255-3924 CHEMTEL International 813-248-0585

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2A

Respiratory or skin sensitization: Skin Sens. 1

Hazard Statements:

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Label elements

29 CFR Part 1910.1200

Signal word: Warning**Pictograms:**

Hazard statements

Causes skin irritation

May cause an allergic skin reaction

Causes serious eye irritation

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container to local/regional/national/international regulations.

Hazards not otherwise classified

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 2 of 9

3. Composition/information on ingredients

Mixtures

Hazardous components

CAS No	Components	Quantity
25068-38-6	Epoxy Resin	60 – 100 %
Reach No:	01-2119456619-26-0000	

4. First-aid measures

Description of first aid measures

General information

In case of accident or un-wellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician.

After contact with skin

Gently wash with plenty of soap and water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. In all cases of doubt, or when symptoms persist, seek medical advice.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. alcohol resistant foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

Specific hazards arising from the chemical

Can be released in case of fire: Carbon monoxide, Carbon dioxide (CO₂).

Special protective equipment and precautions for fire-fighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 3 of 9

Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.
Clean contaminated objects and areas thoroughly observing environmental regulations.

Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.)

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

General protection and hygiene measures: refer to chapter 8

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances. Food and animal feedingstuff.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.
Recommended storage temperature: 20°C
Protect against: Light. UV-radiation/sunlight. heat. moisture.

8. Exposure controls/personal protection

Control parameters

Exposure limits

CAS No.	Substance	ppm	mg/m ³	f/cc	Category	Origin
61788-32-7	Hydrogenated terphenyls	0.5	5		TWA (8 h)	REL

Additional advice on limit values

The following/mentioned above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Exposure controls



Appropriate engineering controls

Provide adequate ventilation.

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 4 of 9

Protective and hygiene measures

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible). Standards: EN 166 or 29 CFR 1910.133

Hand protection

In case of prolonged or frequently repeated skin contact:

Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time: \geq 8 h

Butyl rubber. - Thickness of glove material: 0,5 mm

Breakthrough time: \geq 8 h

CR (polychloroprenes, Chloroprene rubber). - Thickness of glove material: 0,5 mm

Breakthrough time: \geq 8 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time: \geq 8 h

PVC (Polyvinyl chloride). - Thickness of glove material: 0,5 mm

Breakthrough time: \geq 8 h

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at: exceeding exposure limit values, aerosol or mist generation.

Suitable respiratory protective equipment: Particulate Respirators, Standard: 42 CFR Part 84 or EN 143

Type: R/N/P-95/99/100

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

No special precautionary measures are necessary.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	liquid
Color:	not determined
Odor:	characteristic

pH-Value: not determined

Changes in the physical state

Melting point/freezing point: not determined

Initial boiling point and boiling range: not determined

Sublimation point: not determined

Softening point: not determined

Pour point: not determined

Flash point: not determined

Sustaining combustion: Not sustaining combustion

Test method

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 5 of 9

Explosive properties

none

Lower explosion limits:

not determined

Upper explosion limits:

not determined

Ignition temperature:

not determined

Auto-ignition temperature

Gas:

not determined

Decomposition temperature:

not determined

Oxidizing properties

none

Vapor pressure:

not determined

Density:

not determined

Water solubility:

not determined

Solubility in other solvents

not determined

Partition coefficient:

not determined

Viscosity / dynamic:

not determined

Viscosity / kinematic:

not determined

Flow time:

not determined

Vapor density:

not determined

Evaporation rate:

not determined

Solvent separation test:

not determined

Solvent content:

not determined

Other information

Solid content:

not determined

10. Stability and reactivity

Reactivity

No information available.

Chemical stability

Stability:

Stable

The product is chemically stable under recommended conditions of storage, use and temperature.

Can polymerise exothermically in the absence of stabilisers, particularly in acid conditions or if shelf life exceeded.

Possibility of hazardous reactions

Hazardous reactions:

Will not occur

No information available.

Conditions to avoid

Protect against: UV-radiation/sunlight. heat.

Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong.

Hazardous decomposition products

Can be released in case of fire: Carbon monoxide, Carbon dioxide (CO₂).

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 6 of 9

11. Toxicological information

Information on toxicological effects

Route(s) of Entry

Ingestion: May be harmful. Inhalation: May be harmful. Skin contact: Causes skin irritation. May cause sensitisation by skin contact. Eye contact: Causes eye irritation

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Components			
	Exposure route	Dose	Species	Source
25068-38-6	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2-(chloromethyl)oxirane			
	oral	LD50 >5000 mg/kg	Rat (OECD 420)	RTECS
	dermal	LD50 >5000 mg/kg	Rat (OECD 402)	ECHA Dossier

Irritation and corrosivity

Causes skin irritation
Causes serious eye irritation

Sensitizing effects

May cause an allergic skin reaction

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

In-vitro mutagenicity:

Method:

- OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay): negative.

- bacterial reverse mutation assay (e.g. Ames test): positive.

literature information: ECHA dossier

In-vivo mutagenicity:

Method: - ;

Result: negative. ; literature information: ECHA dossier

Carcinogenicity:

Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

species: Rat female. ; Exposure duration: 2 years

Result: NOAEL = 15 mg/kg (reduced body weight), NOAEL = 100 mg/kg (Toxicity)

literature information: ECHA dossier

Reproductive toxicity:

Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); species: Rat

Results: NOEL = 750 mg/kg; literature information: ECHA Dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); species: Rat

Results: NOAEL = 180 mg/kg; literature information: ECHA Dossier

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 7 of 9

Based on available data, the classification criteria are not met.

Subchronic oral toxicity:

Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Species: Rat ; Exposure duration: 90d

Result: NOAEL = 50 mg/kg; literature information: ECHA Dossier

Carcinogenicity (NTP):	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Carcinogenicity (IARC):	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by IARC.
Carcinogenicity (OSHA):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

12. Ecological information

Ecotoxicity

The product has not been tested.

Persistence and degradability

The product has not been tested.

Bioaccumulative potential

No indication of bioaccumulation potential.

Mobility in soil

No data available.

Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

13. Disposal considerations

Waste treatment methods

Advice on disposal

Observe in addition any national regulations! Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

US DOT 49 CFR 172.101

Proper shipping name:

Not a hazardous material with respect to these transport regulations. && Not controlled under DOT

Marine transport (IMDG)

UN number:

No dangerous good in sense of this transport regulation.

UN proper shipping name:

No dangerous good in sense of this transport regulation.

Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Packing group:

No dangerous good in sense of this transport regulation.

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 8 of 9

Air transport (ICAO-TI/IATA-DGR)

UN number:	No dangerous good in sense of this transport regulation.
UN proper shipping name:	No dangerous good in sense of this transport regulation.
Transport hazard class(es):	No dangerous good in sense of this transport regulation.
Packing group:	No dangerous good in sense of this transport regulation.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

Special precautions for user

refer to chapter 6-8

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not relevant

15. Regulatory information

U.S. Regulations

Inventory TSCA

National regulatory information

SARA Section 311/312 Hazards:

Epoxy Resin (25068-38-6): Immediate (acute) health hazard

MBS Rubber (25053-09-2): Immediate (acute) health hazard

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information

Hazardous Materials Information Label (HMIS)

Health:	*2
Flammability:	1
Physical Hazard:	1
Personal Protection:	B

NFPA Hazard Ratings

Health:	1
Flammability:	1
Reactivity:	1
Unique Hazard:	



Changes

Revision date:	27.10.2023
Revision No:	1.01
Rev. 1.0; Initial release:	18.02.2021

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

SAFETY DATA SHEET

according to 29 CFR 1910.1200(g)

Stick Fast Epoxy 329 Resin

Revision date: 27.10.2023

Product code 319 20 min epoxy

Page 9 of 9

CAS Chemical Abstracts Service
DNEL: Derived No Effect Level
IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
International Carriage of Dangerous Goods by Road
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organization
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL: Lowest observed adverse effect level
LOAEC: Lowest observed adverse effect concentration
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
NOAEL: No observed adverse effect level
NOAEC: No observed adverse effect level
NTP: National Toxicology Program
N/A: not applicable
OSHA: Concerning the International Transport of Dangerous Goods by Rail)
PNEC: predicted no effect concentration
PBT: Persistent bioaccumulative toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
SARA: Superfund Amendments and Reauthorization Act
SVHC: substance of very high concern
TRGS Technische Regeln für Gefahrstoffe
TSCA: Toxic Substances Control Act
VOC: Volatile Organic Compounds
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

Other data

Classification according 29 CFR Part 1910.1200 - Classification procedure:
Health hazards: Calculation method.
Environmental hazards: Calculation method.
Physical hazards: On basis of test data. and / or calculated. and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)