

# STICK FAST ADHESIVES

Safety Data Sheet: 351- Red Dye

## Material Safety Data Sheet

U. S. Department of Labor

|  |  |
|--|--|
| IDENTIFY (As used on label)<br><b>Stick Fast: 351-Red Dye for Stabilizing Resin</b>                                |  |
| <b>Section I</b>   |  |
| Name<br><b>TMI Products Inc<br/>Stick Fast Inc.</b>  | Emergency Telephone Number<br>CHEMTEL:<br>888-255-3924<br>813-248-0585 |
| Address (Number, Street, City, State and ZIP Code)<br>308 D Bob Industrial Dr. Suite 8<br>Peachtree City, GA 30269 | Telephone Number for Information<br>(770)-631-7897                     |
|  | Data Prepared<br>04-30-2013 Revised ; 11-02-2023 version 1.1           |

**HMIS RATINGS: HEALTH: 1 Fire: 1 Reactivity 0 Personal Protection: F**

### SECTION 1: PRODUCT IDENTIFICATION

**Product I.D.:** 351-Red

**Product Name:** Red Dye for Stabilizing Resin

**Product Description:** Powdered Solvent Red Colorant

**Chemical Family:** Azo dye

**CAS Number:** 85-86-9

### SECTION 2: HAZARD IDENTIFICATION AND EMERGENCY OVERVIEW

**Emergency Overview:**

With unprotected contact may be eye, skin, respiratory irritant. Possibility of skin sensitization. Follow section 8 instructions for skin protection.

**Eye Contact:**

Unprotected eye contact may be cause of possible irritation and other effects. Follow all supervisor instructions and Personal Protection recommendations in Section 8 of this SDS.

**Skin Contact:**

Unprotected skin contact may cause irritation or other effects. Follow all supervisor instructions and Personal Protection recommendations in Section 8 of this SDS.

**Inhalation:**

Inhalation of product dust or vapors may cause irritation of nose, throat, lungs and mucous membranes. May cause other respiratory effects. Follow all instructions for respiratory protection in Section 8.

**Ingestion:**

Depending on amount swallowed, product can cause mild irritation of mouth, throat, esophagus, stomach, and gastrointestinal tract. Effects may include upset stomach, abdominal discomfort, nausea, vomiting, gastrointestinal disturbances, dizziness, diarrhea, or other

**Medical Conditions Aggravated by Exposure:**

Unprotected contact with product vapors, mists, aerosols, liquids, splashes or dusts may be cause of possible aggravation of pre-existing conditions or diseases of the respiratory system, skin, or eyes. Individuals with above-noted conditions or known or suspected chemical sensitivities or allergies should avoid working with chemicals..

# STICK FAST ADHESIVES

## Safety Data Sheet: 351- Red Dye

### Skin Sensitization:

Contact may cause possibility of skin sensitization in some individuals. Effects may include redness, swelling, itching, rash and hives. It may take repeated or prolonged contact to cause symptoms. Sensitization effects may be unpredictable. If symptoms appear, IMMEDIATELY REMOVE PERSON FROM AREA OF CONTACT and follow Section 4 instructions. In rare cases, if reaction becomes severe, GET IMMEDIATE MEDICAL ATTENTION, as a precaution. Persons known to have or suspected of having chemical sensitivity should not work with dyes or other chemicals. **Respiratory Sensitization:**

Not known to cause respiratory sensitization. With careful handling and good chemical hygiene procedures being followed, no harmful effects are expected. As a precaution against unforeseen or unexpected sensitivity or possible allergic reactions, follow ALL Personal Protection instructions in Section 8 of this SDS. All PPE must be cleaned and maintained after each shift. All exposures should be avoided. Individuals known to be, or suspected to be sensitive to chemical exposure should not work with chemicals. **Special Warnings:**

None for this material

### Unusual Health Hazards:

None for this material

### Supplemental Hazard

No additional information is currently available

**Notes to Physician:** Treat symptomatically based on Section 2 Hazard Warnings and Section 3 ingredients unless indicated otherwise

**Cancer Information:** \*\*\* Not known to contain carcinogens \*\*\*

| Component | CAS Number | Wt %    | IARC   | NTP/OSHA | ACHIH |
|-----------|------------|---------|--|----------|-------|
| Red Dye   | 85-86-9    | 100.00% | Group 3: Unclassifiable on human carcinogenicity | None     | None  |

## SECTION 3: OSHA HAZARDOUS INGREDIENTS

| Component | CAS Number | Wt %    | OSHA-PEL                                    | ACGIH- TLV                                  | Recommended PEL |
|-----------|------------|---------|---|---|-----------------|
| Red Dye   | 85-86-9    | 100.00% | 15mg/m3 TWA Total dust<br>5mg/m3 Respirable | 10mg/m3 TWA Total dust<br>3mg/m3 Respirable | Not applicable  |

### Important Notice:

Unprotected contact with ingredients listed in Section 3 may be hazardous based on OSHA 29 CFR 1910.1200 & related appendices. Components not listed are trade secrets, non-hazardous, or not reportable. This SDS is not intended to offer full disclosure, but all component information is available to medical or emergency personnel. All hazards are based on contact exposure. Effects may be unpredictable and may vary from person to person due to individual reactions. Reducing or eliminating contact can reduce or eliminate risk. Use protective equipment and clothing in Section 8 to minimize or eliminate contact. Users are responsible for hazard determination and communication. Unless indicated otherwise, non-carcinogenic components are indicated within a 1-10% range, and investigated or potential carcinogens within a 0.1-1% range. HMIS ratings are based on data interpretation, and vary from company to company. They are intended only for quick, general identification of the degree of potential hazards. Hazards range from 0 (Minimal) up to 4 (Severe). Consult the National Paint & Coatings Association HMIS Manual for detailed information on ratings. To handle material safely, consider all information in this SDS.

## SECTION 4: FIRST AID INSTRUCTIONS

### Eye Contact:

Immediately rinse with flowing water for at least 15 minutes while holding eyelids open. Get immediate medical attention, as a precaution.

### Skin Contact:

Immediately remove contaminated clothing. Wash affected area with soap and rinse with plenty of water. Get medical attention, as a precaution

### Inhalation:

Immediately move person to fresh air. If breathing is difficult give oxygen, call 911, calm the individual. If not breathing, call 911, give artificial respiration (CPR) until medical help arrives. Have this Safety Data Sheet available.

### Ingestion:

Do not induce vomiting unless directed to do so by a doctor or by other emergency medical personnel. Forced vomiting of certain chemicals may cause aspiration and lung damage. Have this Safety Data Sheet available.

## SECTION 5: FIRE FIGHTING INSTRUCTIONS

**Unusual hazards:** None expected

**Other Hazards:** None known

**Types of Extinguishers:** CO<sub>2</sub>, dry chemical, foam, water fog or spray depending on type of fire

**Fire Fighting Directions:** Wear self-contained breathing equipment and fire-proof clothing. Use water spray to cool fire exposed containers if they cannot be safely moved.

# STICK FAST ADHESIVES

Safety Data Sheet: 351- Red Dye

## SECTION 6: ACCIDENTAL SPILL OR RELEASE INSTRUCTIONS

### **Special Precautions:**

None known. Follow general precautions shown below.

### **Static Discharges:**

**IMPORTANT - GUARD AGAINST FIRE AND EXPLOSION:** Take precautionary measures against static discharges when cleaning up leaks or spills of powders, combustibles, or flammable liquids. Containers should be properly grounded with metal straps, cables or other appropriate means to relieve static electricity build-up or generation. **IMPORTANT:** When using, mixing, filling, or otherwise dispensing any types of solvents, do not allow buildup of flammable or combustible vapors or vapor-air mixtures in confined spaces, storage tanks, or any other areas or enclosures. Totes, drums and all other containers should be completely sealed when not in use. Vapors can travel a distance to ignition sources and cause fire or explosion. Take every precaution and monitor all safety factors and systems, including maintaining more-than-adequate air-exchange ventilation.

### **Environmental Protection:**

Immediately dike liquid spills with inert absorbent material (sand, "Oil Dry" or other commercially available spill absorbent) to contain and soak up liquid. Prevent material from entering floor drains, sewers, or any bodies of water. For powder spills, use sweeping compound, sawdust, or other appropriate material to contain dust. If possible, recover any uncontaminated materials to re-use.

### **Protective equipment and clothing:**

Wear all proper personal protective equipment and clothing to care for spill situation. See section 8 of this Safety Data Sheet.

### **Clean up:**

After containing liquid spill by diking and soaking up with inert absorbent material, place in labeled container to be sealed for proper and regulated disposal. Only the slightest residue should remain. Try to save uncontaminated material for reuse whenever possible. For powders, use sweeping compound to minimize dust and pick up as much product as possible. Do not allow liquids to seep into drains, sewers, lakes, rivers, etc. Check Sections 1 and 2 for dye description or type. Solvent dye residue may be cleaned by scrubbing with detergent, depending on type. Do not add water to water-soluble dyes. Dye is concentrated. This will increase amount of color to remove. All cleaning or scrubbing liquids used should be absorbed and placed in labeled containers for correct disposal. Absorbent material containing solvents may release combustible or flammable vapors and should be handled accordingly, properly labeled and disposed. Check Sections 2, 5, 13 & 15 for applicable instructions and regulations.

## SECTION 7: HANDLING AND STORAGE

### **Warnings and Precautions:**

No special precautions anticipated. Wear all PPE in section 8 as a precaution, and avoid physical contact with material.

### **Personal Protection:**

Wear ALL proper personal protective equipment as outlined in section 8 of this SDS.

### **Handling, Storage & Temperature Conditions:**

Keep containers tightly sealed in cool & dry area, out of direct sunlight. **IMPORTANT: FOR PRODUCTS LISTING FLAMMABLE/COMBUSTIBLE SOLVENTS or LOW FLASH POINTS - GUARD AGAINST FIRE AND EXPLOSION:** Store away from fire hazards and ignition sources, high heat, open flames, welding, hot plates, steam pipes, radiators, etc. Maintain good ventilation. Guard against static discharges. Ground all containers before mixing or filling. Use non-sparking tools to open, close or otherwise work with containers. Limit indoor storage to approved areas with automatic sprinklers. Vapors expected to be released when material is heated during process operations.

**STATIC CHARGES:** Take precautionary measures against static discharges when mixing, cleaning, filling or otherwise dispensing combustible or flammable liquids. Containers should be properly grounded with metal straps, cables or other appropriate means to relieve static electricity build-up or generation.

**VAPORS: IMPORTANT: DO NOT ALLOW** buildup of flammable or combustible vapors or vapor-air mixtures in confined spaces, storage tanks, or any other areas or enclosures. Totes, drums and all other containers should be completely sealed when not in use. Vapors can travel a distance to ignition sources and cause fire or explosion. Take every precaution and monitor all safety factors and systems, including maintaining more-than-adequate air-exchange ventilation.

**POWDERS:** General precautions: Although unlikely in most instances, **GUARD AGAINST DUST EXPLOSION HAZARD.** Eliminate or keep dust to a minimum. Under the right conditions, high dust concentrations of certain particle sizes mixed with air in a critical ratio in the presence of an ignition source can theoretically cause a dust explosion. Be sure to **PROPERLY** ground containers when filling, mixing or otherwise dispensing powders. **KEEP WORK AREA CLEAN AND DUST-FREE.** Follow all Section 8 recommendations for Exposure Controls and Personal Protection.

# STICK FAST ADHESIVES

Safety Data Sheet: 351- Red Dye

## SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Note: Selecting protective equipment & clothing:

When choosing personal protective equipment and clothing, consider each worker's environment, all chemicals being handled, temperature, ventilation, and all other conditions. Determination of the level of protection needed for the eyes, skin and respiratory system under working conditions is the responsibility of the product end-user or shift supervisor. SDS Sections 2, 3, 8 and 11 should be consulted.

### Eye protection:

As a precaution, wear indirectly vented, splash-proof chemical safety goggles. When handling liquids, wear splash-proof goggles under a clear face-shield. Face shield is not to be used without these goggles. The type or extent of protection needed should be determined by the product end-user or shift supervisor.

### Skin Protection:

Always wear impervious, chemical-resistant synthetic or rubber gloves. Check with manufacturer for best glove for the material being handled. Wear good quality long sleeved work shirt, coveralls, and a rubber or plastic apron. Wash hands after handling and before eating, drinking or using restroom. Shower after each shift. Clean contaminated but reusable protective equipment and clothing before reusing and wearing again. Discard contaminated disposable gloves and clothing. The type or extent of protection needed should be determined by the product end-user or shift supervisor.

### Respiratory Protection:

Depending on type of material handled and processing conditions, it is recommended that an appropriate NIOSH approved organic vapor/mist respirator, or dust respirator (with proper filters as required) be worn when exposure to product is expected. After each shift or when equipment becomes contaminated, clean respirator and replace filters in compliance with 29 CFR 1910.134. The type or extent of protection needed should be determined by the product end-user or shift supervisor.

### Eye Washes and Other Protection:

Eye wash stations and drench showers should be located within 100 feet or 10-second walk of the work area per ANSI standard Z358.1-1990.

### Ventilation:

Local exhaust or other appropriate ventilation should be used to maintain exposure limits below specified amounts recommended by OSHA, NIOSH, or ACGIH and to draw spray, aerosol, vapors, or dusts away from workers and prevent routine inhalation. At least 10 air changes per hour are recommended for good room ventilation. **IMPORTANT - GUARD AGAINST FIRE AND EXPLOSION:** When using, mixing, filling, or otherwise dispensing any types of solvents, do not allow buildup of flammable or combustible vapors or vapor-air mixtures in confined spaces, storage tanks, or any other areas or enclosures. Totes, drums and all other containers should be completely sealed when not in use. Vapors can travel a distance to ignition sources and cause fire or explosion. Take every precaution and monitor all safety factors and systems, including maintaining more-than-adequate air-exchange ventilation.

**Airborne Exposure Limits: Not referenced in literature**

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

|  |   |
|--|---|
| pH:  | Not established   |
| % Total VOC:   | 0   |
| % Total Solids / Non-Volatiles:                              | 100%  |
| Appearance:  | Red to reddish brown powder                             |
| Bulk Density:  | 0.10 g/cc (g/cm <sup>3</sup> )                          |
| Odor:  | None  |
| Freezing/Melting Point:                                      | 170°F   |
| % Total VOC:   | 0   |
| Flash Point:   | Not applicable  |
| Solubility:  | Insoluble in water. Soluble in certain organic solvents |
| Other Properties:  | No further data   |
| Other Components:  | Not applicable  |
| Decomposition Temperature:                                   | Not Established   |
| All Data shown above are typical values, not specifications. |   |

# STICK FAST ADHESIVES

Safety Data Sheet: 351- Red Dye

## SECTION 10: STABILITY AND REACTIVITY

### Stability:

Product is expected to be stable under normal, ambient (controlled) conditions concerning heat, moisture, pressure, fire and ignition hazards, and ventilation. Contact with incompatible or reactive materials may cause hazardous reactions in some products if indicated. Check information below.

### Hazardous Polymerization:

Product will not undergo polymerization.

### Conditions to Avoid:

Incompatibles

### Incompatible Materials:

Strong oxidizers.

### Hazardous Decomposition Products:

In fire: oxides of carbon & nitrogen

### Possible Hazard Reactions:

None known

## SECTION 11: TOXICOLOGICAL INFORMATION

| Component | Eye Effect      | Skin Effect     | Skin Sens              | Resp Sens | Oral LD50          | Inh LC50 | Mutagen | Other tox data | Other info                  |
|-----------|-----------------|-----------------|------------------------|-----------|--------------------|----------|---------|----------------|-----------------------------|
| Red Dye   | May be irritant | May be irritant | Sensitization expected | No Data   | > 5000 mg/kg (Rat) | No Data  | No Data | No Data        | May be respiratory irritant |

## Section 12 ECOLOGICAL DATA

\*\*\*\*\* NONE\*\*\*\*\*

## SECTION 13: DISPOSAL AND ENVIRONMENTAL CONSIDERATION

### Reuse of materials:

Reclaim all uncontaminated material to reuse, recycle or otherwise rework whenever possible.

### Contain - Do not release:

Do not release into sewers, water systems, ground systems or ecosystems without proper authorization.

### Disposal Methods:

Incinerate, treat, or bury (landfill), after sampling and testing, at facility approved by applicable federal, state, and local authorities

### Empty Containers:

Empty containers may contain residue and/or vapors and should not be reused unless professionally cleaned and reconditioned. Crush if not cleaned, to prevent reuse.

### Applicable Regulations:

See Section 15 if regulated

### Special Instructions:

See Section 15 if regulated

# STICK FAST ADHESIVES

Safety Data Sheet: 351- Red Dye

## SECTION 14: SHIPPING AND TRANSPORTATION INFORMATION

**DOT Regulations (Ground):**

NOT REGULATED

**IATA Regulations (Air):**

NOT REGULATED

**IMDG / IMO Regulations (Water):**

NOT REGULATED

## SECTION 15: REGULATORY INFORMATION

| Component | CAS number | Weight % | Regulatory List                    |
|-----------|------------|----------|------------------------------------|
| Red Dye   | 85-86-1 9  | 100      | No listings known to be applicable |

**SARA 311/312 Hazard Categories:**

**Immediate/Acute Health Hazard:** NO  
**Chronic/Delayed Hazard:** Yes  
**Fire Hazard:** NO  
**Sudden Release of Pressure Hazard:** NO  
**Reactivity Hazard:** NO

**OTHER:**

No additional information applies, or no supplemental information is available at this time.

**Disclaimer:**

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. This Material Safety Data Sheet was prepared to comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200, and supersedes any previous information. Previously dated sheets are invalid and inapplicable.

END OF MSDS