

Stick Fast Premium DeBonder

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue:

t Regulation (EC) No 1907/2006 /

Revision date: 09/01/2023 Version: 1.20

Safety Data Sheet

Stick Fast 122 Premium DeBonder

V1.2 Revision date: 09.01.2023

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Stick Fast 122 Premium DeBonder UPC sku: 830314001222

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Industrial and professional use to DeBond Cyanoacrylate Adhesives

Uses advised against any non-intended use. Not a Cyanoacrylate Thinner

1.3. Details of the supplier of the safety data sheet

Company name:	TMI Products Inc dba Stick Fast
Place:	308 D Bob Industrial Dr; suite 8 Peachtree City, GA 30269
Telephone: Internet:	770-631-7897 / www.stickfast.com
Responsible Department:	info@stickfast.com Customer Service

1.4. Emergency telephone number:

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTEL): 1-888-255-3924 1-813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3

Acute toxicity: Acute Tox. 4

Hazard Statements:

Flammable liquid and vapor.

Harmful if swallowed.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label

nitrocarbols

Signal word:

Warning

Pictograms:



Hazard statements

H226

Flammable liquid and vapor.

H302

Harmful if swallowed.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233

Keep container tightly closed.

P501

Dispose of waste according to applicable legislation.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 2 of 10

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
75-52-5	nitrocarbol			80 -90 %
	200-876-6	609-036-00-7		
	Flam. Liq. 3, Acute Tox. 4; H226 H302			

Full text of H and EUH statements: see section 16.

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove affected person from the danger area and lay down. Provide fresh air. In case of breathing difficulties administer oxygen. In case of irregular breathing or respiratory arrest provide artificial respiration. Call a physician immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Do not subject to friction.

After ingestion

Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. If swallowed, immediately drink: milk. Water. Caution if victim vomits: Risk of aspiration! Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Handling larger quantities.: Inhalation causes narcotic effects/intoxication.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray. Carbon dioxide. Extinguishing powder. alcohol resistant foam. Dry extinguishing powder.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapors may form explosive mixtures with air. Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium Debonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 3 of 10

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear personal protection equipment. (See section 8.) Remove all sources of ignition. Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains.

6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Take precautionary measures against static discharges. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Use only antistatically equipped (spark-free) tools.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Protect against: UV-radiation/sunlight. Flammable vapors can accumulate in head space of closed systems. Handle with care - avoid bumps, friction and impact.

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Keep under nitrogen.

Advice on storage compatibility

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Handle with care - avoid bumps, friction and impact.

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 4 of 10

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
75-52-5	Nitromethane	100	254		TWA (8 h)	WEL
		150	381		STEL (15 min)	WEL

8.2. Exposure controls**Appropriate engineering controls**

Use only in well-ventilated areas.

Protective and hygiene measures

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

In case of prolonged or frequently repeated skin contact:

Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,5 mm

Breakthrough time \geq 480 min.

penetration time (maximum wearing period): \geq ~160 min.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

insufficient ventilation.

exceeding exposure limit values

Generation/formation of aerosols

Suitable respiratory protective equipment:

gas filtering equipment (EN 141). Type : A

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Environmental exposure controls

The usual precautions for handling chemicals should be considered.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: liquid colorless
 Color: Odor: characteristic

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 5 of 10

Test method

pH-Value: not determined

Changes in the physical state

Melting point: -29 (nitrocarbol) °C

Initial boiling point and boiling range: 101 (nitrocarbol) °C

Flash point: 36 (nitrocarbol) °C

Sustaining combustion: No data available

Explosive properties

not determined

Lower explosion limits: 7,1 (nitrocarbol) vol. %

Upper explosion limits: 63 (nitrocarbol) vol. %

Ignition temperature: 415 (nitrocarbol) °C

Decomposition temperature: not determined

Oxidizing properties

none

Vapor pressure:
(at 20 °C) 36 (nitrocarbol) hPaVapor pressure:
(at 50 °C) 155 (nitrocarbol) hPa

Density: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Flow time: not determined

Vapor density: not determined

Evaporation rate: not determined

Solvent separation test: not determined

Solvent content: 80-90%

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Risk of explosion by shock, friction, fire or other sources of ignition. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Reacts with : Acid. Strong acid. amines. aldehydes. ketone. Base. Lead. Acetone. metal. copper. Reducing agent.

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium D Bonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 6 of 10

10.6. Hazardous decomposition products

In use, may form flammable/explosive vapor-air mixture. Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetic, metabolism and distribution**

No information available.

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1044,4 mg/kg

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
75-52-5	nitrocarbol					
	oral	LD50	940 mg/kg	Rat		GESTIS
	dermal	LD50	>2000 mg/kg	Rabbit		ECHA Dossier
	inhalative (1 h) vapor	LC50 mg/l	[LCLo>12,75]	Rat		ECHA Dossier

Irritation and corrosivity

Based on available data, the classification criteria are not met.
Irritant effect on the eye: slightly irritant but not relevant for classification.
Irritant effect on the skin: Not an irritant.

Sensitizing effects

Based on available data, the classification criteria are not met.
no danger of sensitization.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.
nitrocarbol:
Chronic inhalative toxicity
Exposure time: 24 months.
Species: Rat
Results: NOAEC: >200ppm
literature information ECHA Dossier

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.
nitrocarbol:
In-vitro mutagenicity:
Method:
- OECD Guideline 471 (Bacterial Reverse Mutation Assay) (reliability scoring based on 1997 guideline)
- OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Result: negative.
literature information: ECHA dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 7 of 10

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name	Method	Dose	[h] [d]	Species	Source
	Aquatic toxicity					
75-52-5	nitrocarbol					
	Acute fish toxicity	LC50	>659 mg/l	96 h	Pimephales promelas	ECHA Dossier
	Acute algae toxicity	ErC50	>102 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA Dossier
	Acute crustacea toxicity	EC50	>103 mg/l	48 h	Daphnia magna	ECHA Dossier

12.2. Persistence and degradability

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
75-52-5	nitrocarbol				
	OECD 301D / EEC 92/69 annex V, C.4-E		9,9%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).				

12.3. Bio accumulative potential**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-52-5	nitrocarbol	0,17

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Observe in addition any national regulations! Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled.

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances. Classified as hazardous waste.

Waste disposal number of used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances. Classified as hazardous waste.

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 8 of 10

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN 1261
14.2. UN proper shipping name: NITROMETHANE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: E

Inland waterways transport (ADN)

14.1. UN number: UN 1261
14.2. UN proper shipping name: NITROMETHANE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1261
14.2. UN proper shipping name: NITROMETHANE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Marine pollutant: NO
 Special Provisions: 26

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 9 of 10

Limited quantity: 1 L
 Excepted quantity: E0
 EmS: F-E, S-D

Air transport (ICAO)

14.1. UN number: UN 1261
14.2. UN proper shipping name: NITROMETHANE
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A1 A39
 Limited quantity Passenger: Forbidden
 Passenger LQ: Forbidden
 Excepted quantity: E0
 IATA-packing instructions - Passenger: Forbidden
 IATA-max. quantity - Passenger: Forbidden
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

not applicable.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Reactive

CERCLA/SARA Section 313:

Component: nitromethane (nitrocarbol) 75-52-5 80 - 90%

California Proposition 65:



WARNING: This product can expose you to nitromethane, which is known to the State of California to cause cancer.

For more information, go to www.P65Warnings.ca.gov (<https://www.p65warnings.ca.gov/>).

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

Rev. 1.0 Initial release 2.10.2015

STICK FAST ADHESIVES Safety Data Sheet

according to Regulation (EC) No 1907/2006

Stick Fast Premium DeBonder 122

V1.2 Revision date: 09.01.2023

Product code: 122

Page 10 of 10

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 CAS Chemical Abstracts Service
 DNEL: Derived No Effect Level
 IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
 International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
 LOAEL: Lowest observed adverse effect level
 LOAEC: Lowest observed adverse effect concentration
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 NOAEL: No observed adverse effect level
 NOAEC: No observed adverse effect level
 NTP: National Toxicology Program
 N/A: not applicable
 OSHA: Concerning the International Transport of Dangerous Goods by Rail)
 PNEC: predicted no effect concentration
 PBT: Persistent bioaccumulative toxic
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 SARA: Superfund Amendments and Reauthorization Act
 SVHC: substance of very high concern
 TRGS Technische Regeln für Gefahrstoffe
 TSCA: Toxic Substances Control Act
 VOC: Volatile Organic Compounds
 VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
 WGK: Wassergefährdungsklasse

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport, and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the TMI Products Inc DBA Stick Fast Inc from its suppliers, and because TMI Products Inc DBA Stick Fast Inc has no control over the conditions of handling and use, TMI Products Inc DBA Stick Fast Inc makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and TMI Products Inc DBA Stick Fast Inc assumes no responsibility for use or reliance thereon. It is the responsibility of the user of TMI Products Inc DBA Stick Fast Inc products to comply with all applicable federal, state and local laws and regulations.